

**OMS 61**  
FLEJADORA NEUMÁTICA

**TOOLS**

Flejadora neumática  
para flejar con unión.



**MODELO**

Código	Tipo	Fleje	Espesor
T611943	OMS 61 19 mm 9000N 3B	R 850 N/mm <sup>2</sup> R 1100 N/mm <sup>2</sup>	0.6 mm 0.024" 1.1 mm 0.039" 0.63 mm 0.025" 0.9 mm 0.031"
T612543	OMS 61 25 mm 15000N 3B	R 850 N/mm <sup>2</sup> R 1100 N/mm <sup>2</sup>	0.6 mm 0.024" 1.1 mm 0.039" 0.63 mm 0.025" 0.9 mm 0.031"
T613243	OMS 61 32 mm 15000N 3B	R 850 N/mm <sup>2</sup> R 1100 N/mm <sup>2</sup>	0.6 mm 0.024" 1.1 mm 0.039" 0.63 mm 0.025" 0.9 mm 0.031"

**ESPECIFICACIONES**

**Dimensiones y peso :**

Largo	430 mm 16.9"
Ancho	260 mm 10.2"
Alto	310 mm 12.2"
Peso	11.3 Kg 25 lbs

**Alimentación :**

Presión de trabajo	4.5 - 7 bar / 65-99 psi
Batería	12 L/s - 25 cuft/min

**Prestaciones :**

Tensionamiento máximo\*

7000 N 4,5 bar 65 psi
9000 N - 15000 N 6,5 bar 95 psi

Velocidad de tensionamiento	12 m/min @ 7000 N
	5 m/min @ 9000 N
	4 m/min @ 15000 N

Tipo de cierre	Sellado doble grapa
Resistencia al cierre	80% de la carga
* variable en función del tipo de fleje	de rotura

**UNIÓN**

