

OMS 62
FLEJADORA NEUMÁTICA

TOOLS

Flejadora neumática
para flejar con unión.



MODELO

Código	Tipo	Fleje	Espesor
T621943	OMS 62 19 mm 9000N 2B	R 850 N/mm ² R 1100 N/mm ²	0.6 mm 0.024" 1.1 mm 0.039" 0.63 mm 0.025" 0.9 mm 0.031"
T622543	OMS 62 25 mm 15000N 2B	R 850 N/mm ² R 1100 N/mm ²	0.6 mm 0.024" 1.1 mm 0.039" 0.63 mm 0.025" 0.9 mm 0.031"
T623243	OMS 62 32 mm 15000N 2B	R 850 N/mm ² R 1100 N/mm ²	0.6 mm 0.024" 1.1 mm 0.039" 0.63 mm 0.025" 0.9 mm 0.031"

ESPECIFICACIONES

Dimensiones y peso :

Largo	430 mm 16.9"
Ancho	260 mm 10.2"
Alto	310 mm 12.2"
Peso	11.3 Kg 25 lbs

Alimentación :

Presión de trabajo	4.5 - 7 bar / 65-99 psi
Batería	12 L/s - 25 cuft/min

Prestaciones :

Tensionamiento máximo*

7000 N 4,5 bar 65 psi
9000 N - 15000 N 6,5 bar 95 psi

Velocidad de tensionamiento	12 m/min @ 7000 N
	5 m/min @ 9000 N
	4 m/min @ 15000 N

Tipo de cierre	Sellado doble grapa
Resistencia al cierre	80% de la carga
* variable en función del tipo de fleje	de rotura

UNIÓN

